

Delay Line Phase Shifter

T050250-01
November 10, 2005
Daniel Sigg

Theory of Operations

The delay line phase shifter uses a variable length stripline to delay the input signal by a selectable amount. Eighteen RF switches are used to route the signal either through fixed delay taps or short bypass paths (see schematics D050339). The fixed delay taps are $\frac{1}{16}$ ns, $\frac{1}{8}$ ns, $\frac{1}{4}$ ns, $\frac{1}{2}$ ns, 1 ns, 2 ns, 4 ns, 8 ns and 16 ns in length. Any delay between 0 ns and 31.9375 ns can be added in steps of 0.0625 ns by using front-panel mounted toggle switches or through a digital interface such as EPICS. Since insertion loss is to be kept small, the RF switches have been specially selected and the stripline has been constructed with as large a copper cross-section as possible. The RF switches are PE4220 silicon-on-sapphire devices from Peregrine Semiconductor and have a nominal insertion loss of 0.1 – 0.2 dB between 10 MHz and 500 MHz. Their 1 dB compression point is at 22 dBm. The striplines are built on a 4 layer board with a total thickness of 0.125". This keeps the layer separation around 30 mils and requires 30 mil traces to yield 50Ω transmission lines. With 3 oz. copper the cross-section becomes 0.87 mm^2 . A 16 ns delay will require a trace length around 2.2 m. With a conductivity of $59.6 \times 10^6 \frac{1}{\Omega \text{m}}$ the resistance will be around $40 \text{ m}\Omega$. It is clear that at RF frequencies skin effects will play a role as well. At 25 MHz the skin depth in copper is about 0.5 mils.

Specifications

	Minimum	Nominal	Maximum
Supply	9 V		24 V
Input power 1 dB compression point		22.5 dBm	20 dBm
Intrinsic delay		3.7 ns	
Steps	0	0.0625 ns	511
Delay per step (design)			
Delay per step (at 50 MHz)	0.02 ns	0.0602 ns	0.10 ns
Differential non-linearity (at 50 MHz)	-0.06 ns		+0.06 ns
Fixed insertion loss (1 MHz to 200 MHz)		2.7 dB	
Variable insertion loss (phase shift < 180 °)	-0.6 dB		1.2 dB
Return loss	14 dB		

Setup

```

Needs["BarCharts`"];
Needs["Histograms`"];
Needs["PieCharts`"];
Needs["ErrorBarPlots`"];
Needs["PlotLegends`"];
Needs["Controls`LinearControl`"];

$TextStyle = {FontFamily -> "Helvetica", FontSize -> 13};

plotopt = PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]},
                           {Thickness[0.007], RGBColor[0, 0, 1]},
                           {Thickness[0.007], RGBColor[0.1, 0.7, 0.2]},
                           {Thickness[0.007], RGBColor[0.5, 0.5, 0.2]}};

pathname = "C:/User/Daniel/Protel/DelayLinePhaseShifter/Data/";
filename1 = pathname <> "Delay_Xns.txt";
filename2 = pathname <> "Power.txt";
filename3 = pathname <> "DelayTaps.txt";

```

Import Data

- **Delay as function of frequency**

```

data = Import[filename1, "Table"];
x = First /@ data;
y[0] = (#[[2]] + i #[[3]]) & /@ data;
y[1/16] = (#[[4]] + i #[[5]]) & /@ data;
y[1/8] = (#[[6]] + i #[[7]]) & /@ data;
y[1/4] = (#[[8]] + i #[[9]]) & /@ data;
y[1/2] = (#[[10]] + i #[[11]]) & /@ data;
y[1] = (#[[12]] + i #[[13]]) & /@ data;
y[2] = (#[[14]] + i #[[15]]) & /@ data;
y[4] = (#[[16]] + i #[[17]]) & /@ data;
y[8] = (#[[18]] + i #[[19]]) & /@ data;
y[16] = (#[[20]] + i #[[21]]) & /@ data;

```

- **Power sweep at 50 MHz**

```

pwrdata = Import[filename2, "Table"];
pwrx = First /@ pwrdata;
pwry = Last /@ pwrdata;

```

- **Delay steps at 50 MHz**

```

dtapdata = Import[filename3, "Table"];
dtapx = First /@ dtapdata;
dtaploss = (#[[2]]) & /@ dtapdata;
dtapphase = Last /@ dtapdata;

```

Functions

```

smooth[l_List, n_: 5] :=  $\frac{\text{Plus} @ \#}{n}$  & /@ Partition[l, n, 1];

unwrap[l_List] := Block[{ret = {l[[1]]}, ofs = 0},
  For[i = 2, i <= Length[l], ++i,
    ofs += Which[l[[i]] - l[[i - 1]] > 180, -360, l[[i]] - l[[i - 1]] < -180, 360, True, 0];
    AppendTo[ret, l[[i]] + ofs]];
  ret];

```

Plot of Insertion Loss Data

```


delays =  $\left\{ \frac{1}{16}, \frac{1}{8}, \frac{1}{4}, \frac{1}{2}, 1, 2, 4, 8, 16 \right\}$ ;
Clear[dbmag];
dbmag[0] := Transpose[{x / 1*^6, dB[y[0]]}];
dbmag[n_] := Transpose[{x / 1*^6, dB[y[n]] / y[0]}];
dbmagall = dbmag /@ delays;

Clear[dbmagsmooth];
dbmagsmooth[n_] := Interpolation[smooth[dbmag[n], 5]]
dbmagsmoothall = dbmagsmooth /@ delays;

```

■ Insertion Loss with No Delay

```
f = dbmagsmooth[0];
Plot[f[x], {x, 6, 194},
 PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]}},
 PlotLabel -> "Zero Delay Insertion Loss",
 FrameLabel -> {"Frequency (MHz)", "Insertion Loss (dB)" },
 PlotRange -> All, Frame -> True, GridLines -> Automatic]
```




■ Insertion Loss as Function of Delay

```

Plot[{dbmagsmoothall[1][x], dbmagsmoothall[2][x], dbmagsmoothall[3][x],
      dbmagsmoothall[4][x], dbmagsmoothall[5][x], dbmagsmoothall[6][x],
      dbmagsmoothall[7][x], dbmagsmoothall[8][x], dbmagsmoothall[9][x]}, {x, 6, 194},
PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]},
                 {Thickness[0.007], RGBColor[0.9, 0, 0]},
                 {Thickness[0.007], RGBColor[0.8, 0, 0]},
                 {Thickness[0.007], RGBColor[0.7, 0, 0]},
                 {Thickness[0.007], RGBColor[0.6, 0, 0]},
                 {Thickness[0.007], RGBColor[0.5, 0, 0]},
                 {Thickness[0.007], RGBColor[0.4, 0, 0]},
                 {Thickness[0.007], RGBColor[0.3, 0, 0]},
                 {Thickness[0.007], RGBColor[0.2, 0, 0]}},
PlotLabel -> "Insertion Loss relative to Zero Delay",
FrameLabel -> {"Frequency (MHz)", "Relative Insertion Loss (dB)" },
PlotRange -> All, Frame -> True, GridLines -> Automatic,
PlotLegend ->
  {"1/16 ns", "1/8 ns", "1/4 ns", "1/2 ns", "1 ns", "2 ns", "4 ns", "8 ns", "16 ns"},
LegendPosition -> {1.05, -0.3},
LegendShadow -> None]


```



```

Plot[{dbmagsmoothall[[1]][x], dbmagsmoothall[[2]][x], dbmagsmoothall[[3]][x],
      dbmagsmoothall[[4]][x], dbmagsmoothall[[5]][x], dbmagsmoothall[[6]][x], dbmagsmoothall[[7]][x]},
      {x, 6, 194}, PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]},
      {Thickness[0.007], RGBColor[0.85, 0, 0]},
      {Thickness[0.007], RGBColor[0.7, 0, 0]},
      {Thickness[0.007], RGBColor[0.55, 0, 0]},
      {Thickness[0.007], RGBColor[0.4, 0, 0]},
      {Thickness[0.007], RGBColor[0.25, 0, 0]},
      {Thickness[0.007], RGBColor[0.1, 0, 0]}},
      PlotLabel -> "Insertion Loss relative to Zero Delay",
      FrameLabel -> {"Frequency (MHz)", "Relative Insertion Loss (dB)" },
      PlotRange -> All, Frame -> True, GridLines -> Automatic,
      PlotLegend -> {"1/16 ns", "1/8 ns", "1/4 ns", "1/2 ns", "1 ns", "2 ns", "4 ns"},
      LegendPosition -> {1.05, -0.3},
      LegendShadow -> None]

```



■ Projected Insertion Loss at 45°, 90°, 180°, 270° and 360°

```

seldel[freq_, phase_: 180] := IntegerDigits[Round[16*^9  $\frac{\text{phase}}{360 \text{ freq}}$ ], 2, 9]


```

```

del45 = {x[[#]], seldel[x[[#]], 45].Reverse[Last /@ Transpose[dbmagall][[#]]]} & /@
Range[16, Length[x] - 2];
del90 = {x[[#]], seldel[x[[#]], 90].Reverse[Last /@ Transpose[dbmagall][[#]]]} & /@
Range[16, Length[x] - 2];
del180 = {x[[#]], seldel[x[[#]], 180].Reverse[Last /@ Transpose[dbmagall][[#]]]} & /@
Range[16, Length[x] - 2];
del270 = {x[[#]], seldel[x[[#]], 270].Reverse[Last /@ Transpose[dbmagall][[#]]]} & /@
Range[24, Length[x] - 2];
del360 = {x[[#]], seldel[x[[#]], 360].Reverse[Last /@ Transpose[dbmagall][[#]]]} & /@
Range[32, Length[x] - 2];

MultipleListPlot[{del45, del90, del180, del270, del360},
PlotLabel → "Insertion Loss at multiple phase shifts",
FrameLabel → {"Frequency (MHz)", "Added Insertion Loss (dB)" },
PlotRange → All, Frame → True, GridLines → Automatic,
PlotLegend → {"45°", "90°", "180°", "270°", "360°"}, 
SymbolStyle → {{RGBColor [1, 0, 0]}, {RGBColor [0, 0, 1]},
{RGBColor [0, 0.6, 0]}, {RGBColor [0.5, 0.3, 0]}, {RGBColor [0.2, 0.3, 0.4]}},
LegendPosition → {0.9, -0.3},
LegendShadow → None]

```



Plot of Delay Data

```

delays = {1/16, 1/8, 1/4, 1/2, 1, 2, 4, 8, 16};

Clear[delay];
delay[n_] := Transpose[{x / 1*^6, 1*^9  $\frac{\text{unwrap}[-\text{Phase}[y[n] / y[0]]]}{360 \, x}$ }];
delayall = delay /@ delays;

Clear[delaysmooth];
delaysmooth[n_] := Interpolation[smooth[delay[n], 5]];
delaysmoothall = delaysmooth /@ delays;

 $1*^9 \frac{\text{unwrap}[-\text{Phase}[y[\#] / y[0]]]}{360 \, x}$  & /@ delays;


d50 = Reverse[Transpose[%][100]];
dseries50 = d50.# & /@ (IntegerDigits[#, 2, 9] & /@ Range[0, 511]);
ddiff50 = Drop[dseries50, 1] - Drop[dseries50, -1];
ListPlot[ddiff50, PlotRange -> All]

{15.2993, 7.60334, 3.80206, 1.8605, 0.942471, 0.481698, 0.242551, 0.12733, 0.0643351}

```

- 16ns Delay as Function of Frequency

```
f = delaysmooth[16];
Plot[f[x], {x, 10, 194},
 PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]}},
 PlotLabel -> "Delay",
 FrameLabel -> {"Frequency (MHz)", "Delay (ns)" },
 PlotRange -> All, Frame -> True, GridLines -> Automatic]
```




■ Delay Taps as Function of Frequency

```

LogPlot[{delaysmoothall[[1]][fr], delaysmoothall[[2]][fr], delaysmoothall[[3]][fr],
  delaysmoothall[[4]][fr], delaysmoothall[[5]][fr], delaysmoothall[[6]][fr],
  delaysmoothall[[7]][fr], delaysmoothall[[8]][fr], delaysmoothall[[9]][fr]}, {fr, 10, 194},
  PlotStyle -> {{Thickness[0.007], RGBColor[1, 0, 0]},
    {Thickness[0.007], RGBColor[0.9, 0, 0]},
    {Thickness[0.007], RGBColor[0.8, 0, 0]},
    {Thickness[0.007], RGBColor[0.7, 0, 0]},
    {Thickness[0.007], RGBColor[0.6, 0, 0]},
    {Thickness[0.007], RGBColor[0.5, 0, 0]},
    {Thickness[0.007], RGBColor[0.4, 0, 0]},
    {Thickness[0.007], RGBColor[0.3, 0, 0]},
    {Thickness[0.007], RGBColor[0.2, 0, 0]}},
  PlotLabel -> "Delay Taps",
  FrameLabel -> {"Frequency (MHz)", "Delay (ns)" },
  PlotRange -> All, Frame -> True, GridLines -> Automatic,
  PlotLegend ->
    {"1/16 ns", "1/8 ns", "1/4 ns", "1/2 ns", "1 ns", "2 ns", "4 ns", "8 ns", "16 ns"},
  LegendPosition -> {1.05, -0.3},
  LegendShadow -> None]

```



Plot of Step Data (at 50 MHz)

```

taploss = Transpose[{dtapx, dtaploss}];
tapphase = Transpose[{dtapx, Unwrap[dtapphase] - dtapphase[[1]]}];
dtapdelay = 1*^9 *  $\frac{1 - \text{Unwrap}[dtapphase] + dtapphase[[1]]}{50*^6}$  / 360;
tapdelay = Transpose[{dtapx, dtapdelay}];
diffdelay = Drop[tapdelay, 1] - Drop[tapdelay, -1];
tapslope = Fit[tapdelay, {ns}, ns] /. ns → 1;
dnldelay = (Range[0, Length[dtapdelay] - 1] tapslope) - dtapdelay;
0.0602106


```

- **Insertion Loss as Function of Steps**

```


ListPlot[taploss,
 Joined → True,
 PlotLabel → "Insertion Loss as Function of Steps at 50 MHz",
 FrameLabel → {"Steps", "Insertion Loss (dB)" },
 PlotRange → All, Frame → True, GridLines → Automatic,
 PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]

```




■ Phase Shift as Function of Steps

```
ListPlot[tappphase,  
 Joined → True,  
 PlotLabel → "Phase as Function of Steps at 50 MHz",  
 FrameLabel → {"Steps", "Phase (°)"},  
 PlotRange → All, Frame → True, GridLines → Automatic,  
 PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]
```




■ Delay as Function of Steps

```
ListPlot[tapdelay,  
 Joined → True,  
 PlotLabel → "Delay as Function of Steps at 50 MHz",  
 FrameLabel → {"Steps", "Delay (ns)"},  
 PlotRange → All, Frame → True, GridLines → Automatic,  
 PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]
```




■ Differential Non-Linearity

```
ListPlot[difftapdelay,  
 Joined → True,  
 PlotLabel → "Delay Step as Function of Steps at 50 MHz",  
 FrameLabel → {"Steps", "Δ Delay (ns)"},  
 PlotRange → {0, 0.08}, Frame → True, GridLines → Automatic,  
 PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]
```




```
ListPlot[dnldelay,
Joined → True,
PlotLabel → "Differential Non-Linearity at 50 MHz",
FrameLabel → {"Steps", "Δ Delay (ns)" },
PlotRange → {-0.06, 0.06}, Frame → True, GridLines → Automatic,
PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]
```



Plot of Power Sweep

■ Insertion Loss as Function of Input Power

```
ListPlot[pwrdata,  
 Joined → True,  
 PlotLabel → "Insertion Loss as Function of Input Power",  
 FrameLabel → {"Input Power (dBm)", "Insertion Loss (dB)"},  
 PlotRange → All, Frame → True, GridLines → Automatic,  
 PlotStyle → {Thickness [0.007], RGBColor [1, 0, 0]}]
```



```
ListPlot[pwrdata,  
Joined -> True,  
PlotLabel -> "Insertion Loss as Function of Input Power",  
FrameLabel -> {"Input Power (dBm)", "Insertion Loss (dB)"},  
PlotRange -> {-3.0, -2.6}, Frame -> True, GridLines -> Automatic,  
PlotStyle -> {Thickness [0.007], RGBColor [1, 0, 0]}]
```

