


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED


# PC RS-232C Serial Port (DB-9 Male)




DB-9 F to RJ-12 F  
CA232

RJ-12 M TO RJ-12 M  
CCRJ12

# ALD118 Serial Port (RJ-12 Female)



## DB-9 Female



Pin	Signal
1	CD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

## DB-9 Female

Pin 2	←
Pin 3	→
Pin 5	←
Pin 1	←
Pin 4	←
Pin 6	←
Pin 7	←
Pin 8	←
Pin 9	←

## RJ-12 Female

Pin 4	←
Pin 3	→
Pin 6	←
Pin 1	←
Pin 2	←
Pin 5	←

no connects


## RJ-12 Jack (Female)



Pin	Signal
1	+5 VDC
2	RS-485 -
3	RXD
4	TXD
5	RS-485 +
6	GND

DO NOT CONNECT PINS 1, 2 OR 5 OF  
MODULAR CONNECTOR TO DB-9.

RJ-12 Female  
Looking into socket



Masterclock, Inc.  
2484 W. Clay St.  
St. Charles, MO. 63301

Tel: +636-724-3666  
Fax: +636-724-3776  
www.masterclock.com

# CA232

## PC Serial to ALD118

SIZE	FSCM NO.	DWG NO.	REV 0
SCALE	1/7/2003	SHEET	