

```

% ALS Locking Strategy
%
% Daniel Sigg's idea using 4 VCO's
%
% Needs the ALS_freq3v3.mdl Simulink model
%
% BS - 10 May 2010
%
% 24 June 2010 - modified the titles to reflect the  $G = b/a$ , e.g. (in 18, out 22/out 20)
% 13 July 2010 - Added more input/output points to get Hz/Hz transfer
%                  functions for VCO noise performance requirements
%

clear all;

% Constants
c = 299792458; % [m/s]

lambda_IR = 1064e-9;
lambda_GRN = 532e-9;

f = logspace(-1, 6, 1e3);

%% Engaging Servo's
FSSengaged = 1;
TTFSSengaged = 1;
PDHengaged = 0;
COMMengaged = 0;
DIFFengaged = 0;

%% Setting up the PSL section
%

% Ref Cav Transmission TF
RefCavFSR = c / (2 * 0.2); % Ref Cav length 20cm?
RefCavFIN = 5000; % Ref Cav Finesse
RefCavPole = 2*pi * RefCavFSR / (2* RefCavFIN); % Ref Cav Pole frequency, 470kHz

% PSL FSS
PSLfrequencyActuator = 1; % This is just a gain for the FSS feedback to the PSL
(Temp, PZT and Pockell)
zzz = [RefCavPole/2/pi];
ppp = [1];
kkk = 10^( 17 /20);
FSS_Servo = zpk(-2*pi*zzz, -2*pi*ppp, -kkk);

% LowNoiseVCO -> FSS low noise VCO driver TF, [Hz/V]
zzz = [];
ppp = 2e6; % Range of the VCO
kkk = ppp / 20; % VCO Full tuning range (2 MHz) / VCO Input voltage range
(+/-20V)
LowNoiseVCO_psl = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

% AOM Driver at fiber launch
AOM_Driver = 1;

%% Setting up the X-End station
%

FiberPhaseNoise = 100; % flat fiber induced phase noise, 100 Hz/rtHz
freqnoiseNPRO = abs(1e4 ./ (1 + i.*f/1)); % Freerunning NPRO, 100 Hz/rtHz at 100 Hz

% Arm Cav Transmission TF
L_arm = 3995;
ArmCavFSR = c / (2 * L_arm); % Ref Cav length 20cm?

```

```

ArmCavFIN = 100; % Ref Cav Finesse
ArmCavPole = 2*pi* ArmCavFSR / (2* ArmCavFIN); % Arm Cav Pole frequency, ~1178 Hz

% LowNoiseVCO,EX -> TTFSS low noise VCO driver TF, used to demodulate the
% heterodyne signal in the end-station
zzz = [];
ppp = 2e6;
kkk = ppp / 20; % VCO Full tuning range (2 MHz) / VCO Input voltage range
(+-20V)
LowNoiseVCO_local = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

% End-Station laser feedback
uPZT_local = 3e6; % PZT Volts to IR Frequency conversion, 3 MHz/V

% TTFSS Servo -> TTFSS Locking Servo, lock the laser to the heterodyne beatnote.
zzz = [ 0 1e3];%[0 0 10 RefCavPole/2/pi];
ppp = [1 1 2e5]; % limited by the feedback to the laser PZT?
kkk = 10^(79/20);
TTFSS_Servo = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

% PDH Servo -> PDH locking servo to lock the laser frequency to the arm cavity
% add notch at 1 Hz, Q=10, depth 30 dB (using foton:)

%- When DIFF and COMM are not engaged
% zzz = [1 300 0.003+i*0.999949 0.003-i*0.999949];
% ppp = [1.001+i*0.994872 1.001-i*0.994872 1e5 1e5];
% kkk = 1000000000000000;%60000000;

zzz = [200 ];
ppp = [1];
kkk = 10^(62/20);
PDH_Servo = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

%% Setting up the Vertex ALS Demodulation
%

% LowNoiseVCO,Comm -> Vertex ALS Common Mode low noise VCO driver TF
zzz = [];
ppp = 2e6; % Frequency range, Hz
kkk = ppp / 20; % VCO Full tuning range (2 MHz) / VCO Input voltage range
(+-20V)
LowNoiseVCO_comm = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

% LowNoiseVCO,Diff -> Vertex ALS Differential Mode low noise VCO driver TF
LowNoiseVCO_diff = zpk(-2*pi*zzz, -2*pi*ppp, kkk);

%% Common Mode Servo -> Common Mode locking servo to lock the PSL frequency
%% to the common mode arm cavity length fluctuations
zzz = [0];
ppp = [1];
kkk = 10^( 126 /20);
CommonMode_Servo = zpk(-2*pi*zzz, -2*pi*ppp, -kkk);

%% Differential Signal Feedback to the ETM Quads
nu_IR = c / lambda_IR;

% Differential Mode Servo
zzz = [0.5];
ppp = [1e6];
kkk = 10^( -50 /20);
DifferentialMode_Servo = zpk(-2*pi*zzz, -2*pi*ppp, -kkk);

%% Setting up the Quad Feedback and Control Block
global pend

% Angular radiation pressure torque coefficients

```

```

k_major = 0;
k_minor = 0;
k_ospring = 0;

gLP = 0;
ServoTM = 0;
ServoPM = 0;
ServoUIM = 0;
ServoTOP = 0;

damper = 1; % ECD
% damper = 2; % GEO Damping
% damper = 3; % Damping with fancy LPF
% damper = 4; % no damping

%*****
ssmake4pv2eMB2; % better blade modeling from MATHEMATICA, Mark Barton
%*****
localdamp;

if ~exist('k_ospring')
    k_ospring = 0;
else
    % MEVANS
    warning('NOT including optical spring. ');
    k_ospring = 0;
end

% Run the Quad Servo Script
PDHservo_All_2010_05_21_11_00_19

% Set the Signal Path Switches
gLP = 0; % Keep the loop open to make it run within the overall simulation
gTM = 1; % engage the TM feedback
gPM = 1; % engage the PM feedback
gUIM = 0; % engage the UIM feedback
gTOP = 0; % engage the TOP feedback

%% Implementing the Simulink Model
%
%modelname = 'ALS_freq3v3';
modelname = 'ALS_freq3v4';
%
[AAA,BBB,CCC,DDD] = linmod2(modelname); % linearise the Simulink model
[rw,cl] = find(AAA == Inf); AAA(rw,cl) = 1e20;
[rw,cl] = find(AAA == -Inf); AAA(rw,cl) = -1e20;
[rw,cl] = find(BBB == Inf); BBB(rw,cl) = 1e20;
[rw,cl] = find(BBB == -Inf); BBB(rw,cl) = -1e20;
[rw,cl] = find(CCC == Inf); CCC(rw,cl) = 1e20;
[rw,cl] = find(CCC == -Inf); CCC(rw,cl) = -1e20;
[rw,cl] = find(DDD == Inf); DDD(rw,cl) = 1e20;
[rw,cl] = find(DDD == -Inf); DDD(rw,cl) = -1e20;

SYS = ss(AAA,BBB,CCC,DDD); % ceates a state-space model of the Simulink
model
% TF = SYS(output, input)

%% Do some test plotting
% a = SYS(27,25);
a = SYS(4,25);
b = SYS(31,4);
figure(99)
% mybodesys(a,f);
%title('VCO\_EX -to- f\_IR\_ex');

```

```

%% Print the Simulink model with all its colours, that works only in
%% Windows!
% set_param(modelname, 'ShowPageBoundaries', 'on');
% print(['-s' modelname], '-dpdf', [modelname '.pdf']); % print the simulink model with
its colors...

%% Obtaining the transfer functions
save_figure = 0; % controls is the figures are save as .pdf or not

save_figure_all = 0;
save_figure_dir = 'sim/';

if save_figure_all
    FSS=1;
    TTFSS=1;
    PDH=1;
    COMM=1;
    DIFF=1;
    save_figure = 1;
    save_figure_dir = 'sim/';
else
    FSS = 0; % Plots the FSS loops of th PSL servo
    if FSSengaged
        FSS = 1;
        save_figure_dir = 'tffss/';
    end
    TTFSS = 0; % Plots the TTFSS loops in the end-station
    if TTFSSengaged
        TTFSS = 1;
        save_figure_dir = 'tffss/';
    end
    PDH = 0; % plots the PDH loops in the end-station
    if PDHengaged
        PDH = 1;
        save_figure_dir = 'pdh/';
    end
    COMM = 0;
    if COMMengaged
        COMM = 1;
        save_figure_dir = 'comm/';
    end
    DIFF = 0;
    if DIFFengaged
        DIFF = 1;
        save_figure_dir = 'diff/';
    end
end % end save_figure

if FSS
%% FSS Feedback of the laser to the Reference Cavity
%
%% % PSL laser -to- FSS error signal
hdl= figure(101)
a = SYS(20,18);
b = SYS(22,18);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('PSL -to- FSS error signal TF (in 18, out 22/out 20)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);

```

```

xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
    % print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), ' ',get(tt,'string'),
'.pdf']);
end

%% % FSS Open Loop response
hdl= figure(102)
a = SYS(21,19);
b = SYS(20,19);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('FSS Controller TF (in 19, out 20/out 21)','FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

%% % FSS Close Loop Response Response
hdl= figure(103)
a = SYS(21,19);
b = SYS(22,19);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('FSS Open Loop TF (in 19, out 22/out 21)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

%% % FSS Supression Response
hdl= figure(104)

```

```

G = mybodesys(SYS(21,19),f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('FSS Suppression Response (in 19, out 21)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

end          % end FSS

if TTFSS
%% TTFSS Feedback of the laser to the Heterodyen Signal
%
% Local laser to TTFSS error signal
hdl= figure(1)
a = SYS(5,8);
b = SYS(3,8);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Local laser -to- TTFSS error signal TF (in 8, out 3/out 5)', 'FontSize',
16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% TTFSS Open Loop response
hdl= figure(2)
a = SYS(6,7);
b = SYS(5,7);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('TTFSS Controller TF (in 7, out 5/out 6)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])

```

```

grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% TTFSS Close Loop Response Response
hdl= figure(3)
a = SYS(6,7);
b = SYS(3,7);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('TTFSS Open Loop TF (in 7, out 3/ out 6)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% TTFSS Supression Response
hdl= figure(4)
G = mybodesys(SYS(6,7),f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('TTFSS Suppression Response (in 7, out 6)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

end          % end TTFSS

if PDH

```

```

%% PDH Feedback of the laser frequency to the arm cavity, via the VCO,EX
%
% Local VCO,EX to PDH error signal
hdl = figure(5)
a = SYS(8,9);
b = SYS(10,9);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('VCO,EX -to- PDH Error Signal TF (in 9, out 10/out 8)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

% PDH Controller response
hdl= figure(6)
a = SYS(9,10);
b = SYS(8,10);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('PDH Controller TF (in 10, out 8/out 9)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

% PDH Close Loop Response Response
hdl = figure(7)
a = SYS(9,10);
b = SYS(10,10);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('PDH Open Loop TF (in 10, out 10/out 9)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on

```

```

subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% PDH Supression Response
hdl = figure(8)
G = mybodesys(SYS(9,10),f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('PDH Suppression Response (in 10, out 9)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

end % end PDH

if COMM
%% Common Mode Feedback of the PSL frequency to the common mode arm cavity
%% length fluctuations, via the VCO,C
%
% Vertex VCO,PSL to Common Mode error signal
hdl = figure(9)
a = SYS(12,12);
b = SYS(13,12);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('VCO,PSL -to- Common Mode Error Signal TF (in 12, out 13/out 13)',
'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

```

```

end

% Common Mode Servo Open Loop response
hdl= figure(10)
a = SYS(11,11);
b = SYS(12,11);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Common Mode Controller TF (in 11, out 12/ out 11)', 'FontSize',16);
ylabel('Mag [dB]', 'FontSize', 14)
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

% Common Mode Close Loop Response
hdl = figure(11)
a = SYS(11,11);
b = SYS(13,11);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Common Mode Open Loop TF (in 11, out 13/out 11)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
% set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

%%

% Common Mode Supression Response
hdl = figure(12)
G = mybodesys(SYS(11,11),f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Common Mode Suppression Response (in 11, out 11)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);

```

```

xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end
end % end COMM

if DIFF
%% Differential Mode Feedback to both the ETMs (out of phase). This
%% requires the Quad response and its servo, for now I have a single
%% pendulum replacing the Quad...
%
% Diff Mode Servo input to Differential Mode error signal
hdl = figure(13)
a = SYS(23,20);
b = SYS(14,20);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Diff Servo Ouput -to- Diff Mode Error Signal TF (in 20, out 14/out 23)',
'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
%   axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
axis([min(f) max(f) -50 250])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%.3d'), '.pdf']);
end

% Diff Mode Controller response
hdl= figure(14)
a = SYS(17,15);
b = SYS(23,15);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Differential Mode Controller TF (in 15, out 23/out 17)', 'FontSize',16);
ylabel('Mag [dB]', 'FontSize', 14)
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');

```

```

    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% Differential Mode Close Loop Response
hdl = figure(15)
a = SYS(17,15);
b = SYS(18,15);
G = mybodesys(b/a,f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), f, 20*log10(50./f), 'LineWidth', 2)
tt= title('Differential Mode Open Loop TF (in 15, out 18/out 17)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
%   axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
axis([min(f) max(f) -100 100])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

% Differential Mode Supression Response
hdl = figure(16)
G = mybodesys(SYS(17,15),f);
%
subplot(211)
semilogx(f,20*log10(abs(G)), 'LineWidth', 2)
tt= title('Differential Mode Suppression Response (in 15, out 17)', 'FontSize', 16);
ylabel('Mag [dB]', 'FontSize', 14);
axis([min(f) max(f) floor(min(log10(abs(G))))*20 ceil(max(log10(abs(G))))*20])
grid on
subplot(212)
semilogx(f,angle(G)*180/pi, 'LineWidth', 2)
ylabel('Phase [deg]', 'FontSize', 14);
xlabel('Freq [Hz]', 'FontSize', 14);
axis([min(f) max(f) 90*floor(min(angle(G)*180/pi)/90) 90*ceil(max(angle(G)*180/pi)/
90)])
%   set(gca,'YTick',[-1800:90:1800])
grid on
if save_figure == 1
    orient(hdl, 'landscape');
    print('-dpdf', [save_figure_dir ,num2str(hdl,'%3d'), '.pdf']);
end

end          % end DIFF

```