



REVISIONS		
REV.	DESCRIPTION	DATE
A	E030526-00-E	10/20/03

- NOTES: UNLESS OTHERWISE SPECIFIED
1. REMOVE ALL BURRS AND BREAK SHARP EDGES TO A MAXIMUM OF .015
 2. PART NUMBER (DRAWING NO., DASH NO., REVISION NO.) TO BE CLEARLY MARKED ON THE PART ITSELF
 3. PAINT:
ALL VISIBLE SURFACES
MEDIUM BLUE SHERWIN WILLIAMS (POLANE (R) T-PLUS POLYURETHANE ENAMEL) # SW-F63TX-L-2822-5864
PRIME WITH SHERWIN WILLIAMS INDUSTRIAL WASH PRIMER P60G2
 4. "OXI SOLV RUST INHIBITOR" TO BE APPLIED PER MFG. INSTRUCTIONS TO ALL UNPAINTED SURFACES.
BOTH TAPPED AND THRU HOLES WILL BE PLUGGED DURING APPLICATION.

RELEASE FOR PRODUCTION, DCN No. E030526, 10.30.03

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: DECIMALS ANGLES .X ± .06 .XX ± .01 ±1 .XXX ± .005	CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY
	APPROVALS	DATE	
	DRAWN M. HAMMOND	10/20/03	HORIZONTAL ANGLE MOUNT BACKUP PLATE HYDRAULIC ISOLATOR
	CHECKED M. HAMMOND	10/20/03	
RESP ENG			
MATERIAL ASTM A36 STEEL	MFG ENG		SIZE B
FINISH SEE NOTES	QUAL ENG		DWG. NO. D030694-A
DO NOT SCALE DRAWING			REV. A
SCALE 1:3.5		CAD FILE: actuator_bracket_backup_plate.dwg	SHEET 1 OF 1