



- NOTES: (UNLESS OTHERWISE SPECIFIED)
- 1. ALL ABRASIVE CUTTING TO BE DONE FROM NEAR SIDE.
  - 2. GLASS TO BE COVERED BY VINYL MASK ON BOTH SIDES PRIOR TO START OF MACHINING, AND REMOVED BEFORE SHIPMENT.
  - 3. MAKE FROM: #12 WELDERS FILTER GLASS (SCHOTT) 0.12" THICK.
  - 4. ETCH OR ENGRAVE THE DRAWING PART NUMBER ON NOTED FACE OF PART FOLLOWED BY "S/N", THEN A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS TO START AT 001 FOR FIRST PART A MAXIMUM OF 999, FOR EACH SUCCEEDING PART PRODUCED. USE 0.13 HIGH CHARACTERS. EXAMPLE: D990038-A S/N 001

DWG. NO.      DESCRIPTION REFERENCE DRAWINGS		MATERIAL: <span style="color: red;">△</span> 3 HEAT TREAT:		FINISH: <span style="color: red;">△</span> 1 <span style="color: red;">△</span> 2 <span style="color: red;">△</span> 4 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR ± 1/2° TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005 INSIDE RADII FINISHED SURFACE RMS BREAK OUTSIDE CORNERS .002 - .010 REMOVE ALL BURRS		A      RELEASE      E990389      -      -      -      KABOT      1-12-00 REV      DESCRIPTION      DCN NUMBER      APPR'D      CHECK      DRWN      DATE		LIGO CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY ARM CAVITY BAFFLE, GLASS 5		CAD FILE      SIZE      DWG. NO. D990497-A.dwg      D      D990497-A	
										USED ON:      NEXT ASS'Y: D980174, D980175, D980176	