

Advanced LIGO The Next Generation

Philip Lindquist, Caltech


XXXVIII Moriond Conference

Gravitational Waves and Experimental Gravity

March 23, 2003


To develop the field

- LIGO infrastructure is in place
 - » Designed to support the evolving field of gravitational wave science
- Initial LIGO is in operation
 - » Sensitivity is improving steadily, approaching goal
 - » Observations are yielding first astrophysical results
- One year of integrated observation time is planned
- Detection is plausible with the initial LIGO
- With or without detection, astrophysical community will want/demand more sensitive detectors




Advanced LIGO

- Next Detector
 - » Must be relevant for astrophysics
 - » Should approach limits of reasonable extrapolations for detector physics and technologies
 - » Should lead to realizable, practical, reliable instrument
 - » Should exist neither too early nor too late
- Advanced LIGO
 - » >10 X sensitivity, ~ 3000 in rate (population density dependent)
 - » **~2.5 hours = 1 year of initial LIGO**




- Neutron Star and Black Hole Binaries
- Spinning Neutron Stars
- NS Birth (Super Novae, AIC)
- Stochastic Background



(Chart by Kip Thorne)

Projected Advanced LIGO Performance

- Suspension thermal noise
- Internal thermal noise
- Newtonian background, estimate for LIGO sites
- Seismic “cutoff” at 10 Hz
- Unified quantum noise dominates at most frequencies for full-power, broadband tuning



Current LIGO

Power recycled

Fabry-Perot to increase storage time

Advanced LIGO


Increased Power

Heavier Test Masses

Quad Suspensions


Improved Isolation

Signal Recycling





Signal Recycling

- Can focus sensitivity where needed
 - » Sub-wavelength adjustments of resonance in signal recycling cavity
- Allows optimization
 - » Technical constraints
 - » Astrophysical signatures




Limits to Sensitivity--Thermal Noise

- Thermal motion is proportional to $\sqrt{L_{\text{mechanical}}}$
- Low-loss materials and techniques needed
 - » Test masses: crystalline sapphire, 40 kg, 32 cm diameter
 - » Suspensions: fused silica
 - » Monolithic final stages
 - » Multiple pendulums for control and seismic attenuation




Optical coating also source of mechanical loss, development underway

- Coupling of seismic noise through isolation system suppressed using active servo controls, passive “pendulum” isolation
 - » Two 6-degree-of-freedom platforms stabilized from 0.03 to 30 Hz
 - » Net suppression of motion in gravitational-wave band is 13 orders of magnitude or more
 - » Suppression of motion below the band also critical to hold sensing system (control) in linear domain, avoid up-conversion



Low-Frequency Limit

- Newtonian background is limit for ground-based detectors (~ 10 Hz)
 - » Time-varying distribution of mass in vicinity of test mass
 - » Seismic compression, rarefaction or earth dominates
 - » Advanced LIGO targeted to reach this limit for our sites
- For GW astrophysics below 10 Hz, space-based instruments needed $\text{\textcircled{R}}$ **LISA**




Submitted February 2003 (NSF PHY-0328418)

- Prepared a “bottoms up” cost estimate (approximately 5000 detailed line items)
- Total Cost Estimate: **\$240,000,000**
- Proposed LIGO Cost **\$122,000,000** (fabrication plus some salaries for installation, specialty engineering, added outreach)
- **\$25.5 million provided by collaborators**
 - » GEO (Hanover, Birmingham, Rutherford, Glasgow)
 - » ACIGA

- Initial LIGO Observation 2002 – 2006
 - » 1+ year observation within LIGO Observatory
 - » Significant networked observation with GEO, LIGO, TAMA
- Structured R&D program to develop technologies 1998 - 2005
 - » Conceptual design developed by LSC in 1998
 - » Current Cooperative Agreement carries R&D to Final Design, 2005
- Proposal submitted in Feb 2003 for fabrication, installation
- Long-lead purchases planned for 2004
 - » Sapphire Test Mass material, seismic isolation fabrication
 - » Prepare a 'stock' of equipment for minimum downtime, rapid installation
- Start installation in 2007
 - » Baseline is a staged installation, Livingston followed by Hanford Observatories
- Start coincident observations in 2009

Proposed Funding Profile

- Long lead procurements begin in 2004
- Procurements peak in 2006
- Installation begins in 2007



The Advanced LIGO Community

- Scientific impetus, expertise, and development provided by LIGO scientific collaboration (LSC)
 - » Synergy, critical mass (400+ individuals, 100+ graduate students, 40+ institutions)
 - » International support and significant material participation
 - » Especially strong collaboration with German-UK GEO group, capital partnership
- Advanced LIGO design, R&D, and fabrication shared with participants
 - » LIGO laboratory leads, coordinates, is responsible for observatories
- Continuing support from NSF at all levels
- International network growing: VIRGO, GEO-600, TAMA, ACIGA

- **Initial LIGO is in operation**
 - » We are preparing publications from first science run
 - » Second science run underway
 - » Third science run at target sensitivity scheduled to begin next year
 - » Discovery plausible
- **Advanced LIGO on the horizon**
 - » Advanced R&D and baseline design proceeding
 - » Strong international partnership—GEO, ACIGA
 - » Plan supports start of installation in 2007

**Gravitational Waves:
new tool for understanding the Universe,
complementary to other observational methods,
becoming a reality**

Acknowledgements

- National Science Foundation
 - » NSF PHY-9210038 (Construction and Initial Operations)
 - » NSF PHY-0107417 (Current Operations)
- Gary Sanders, LIGO Deputy Director
- David Shoemaker, Advanced LIGO Project Lead