

H2 PSL DIODE AND CHILLER ROOM WIRING DIAGRAM

Name	Adpt. 9	D-Sub	D-Sub	Phoenix	Phoenix	Channel	Sensor	Sensor Connector
	F.Pin#	M.Pin#	F.Pin#	M.Pin#	F.Pin#	Analog	Name	Pin#
T7	1	1	1	1	1	24v Inpt.	HX93AC	TB2 Pin(1) TB1 Pin(1)
T7	14	14	14	14	14	Temp. Sig. Out.	HX93AC	TB2 Pin(3)
H3(incl.T7)	2	2	2	2	2	Humidity Sig. Out.	HX93AC	TB1 Pin(3)
T8	3	3	3	3	3	24V Inpt.	HX93AC	TB2 Pin(1) TB1 Pin(1)
T8	16	16	16	16	16	Temp. Sig. Out.	HX93AC	TB2 Pin(3)
H4(incl.T8)	4	4	4	4	4	Humidity Sig. Out.	HX93AC	TB1 Pin(3)
P3	5	5	5	5	5	24v Inpt.	DM-2000	Pin(+)
P3	18	18	18	18	18	Pressure Sig. Out.	DM-2000	Pin(COM)
P4	6	6	6	6	6	24V Inpt.	DM-2000	Pin(+)
P4	19	19	19	19	19	Pressure Sig. Out.	DM-2000	Pin(COM)