


8876T38

Plastic Loop Clamps

An economical way to secure your lines. Fasteners not included.

Clamps for 1/8" to 1/2" OD have an 11/64" dia. mounting hole; clamps for 5/8" to 1 1/2" OD have a 13/64" dia. mounting hole.

Nylon



Nylon

Nylon clamps are nonconductive and noncorrosive. All are Type 6/6 nylon. Temperature range is -40° to +185° F. Meet ASTM D-4066.

For OD	Lg.	Wd.	Thick.	Pkg. Qty.	Black		White	
					Pkg.	Pkg.		
1/8"	11/16"	3/8"	3/64"	100	8876T34	\$5.40	8876T14	\$5.40
3/16"	13/16"	3/8"	3/64"	100	8876T35	5.40	8876T15	5.40
1/4"	13/16"	3/8"	3/64"	100	8876T36	5.33	8876T16	5.33
5/16"	7/8"	3/8"	3/64"	100	8876T37	6.94	8876T17	6.94
3/8"	1"	3/8"	3/64"	100	8876T38	5.84	8876T18	5.84
7/16"	1"	3/8"	3/64"	100	8876T39	6.55	8876T19	6.55
1/2"	1 1/8"	3/8"	3/64"	100	8876T41	7.36	8876T21	7.36
5/8"	1 1/4"	1/2"	3/64"	100	8876T43	10.41	8876T23	10.41
3/4"	1 7/16"	1/2"	3/64"	100	8876T45	10.57	8876T25	10.57
7/8"	1 1/2"	1/2"	3/64"	100	8876T46	12.42	8876T26	12.42
1"	1 5/8"	1/2"	3/64"	100	8876T47	12.82	8876T27	12.82
1 1/8"	1 13/16"	1/2"	3/64"	50	8876T48	12.95	8876T28	12.95
1 1/4"	2 3/16"	1/2"	3/64"	50	8876T49	13.93	8876T29	13.93
1 1/2"	2 5/16"	1/2"	3/64"	50	8876T51	13.87	8876T31	13.87

[91772A191](#)

Pan Head Phillips Machine Screws



18-8 Stainless Steel

Lg.	Pkg. Qty.		Pkg.
8-32—#2 Drive			
1/8"	100	91772A188	10.31
3/16"	100	91772A189	9.06
1/4"	100	91772A190	6.42
5/16"	100	91772A191	6.56
3/8"	100	91772A192	6.88

