




Air Brake D.O.T. Compression Style Fittings for J844 Tubing - NTA | #63NTA-6

 [View Series Page](#)



\$0.80 /part

Local Manufacturer

Parker Hannifin Corporation

Fluid System Connectors Division

200 Parker Drive

300 Parker Drive

Otsego, MI 49078 USA

UNITED STATES

Phone

+1 (269) 692-6555

Fax

+1 (269) 694-4614

Get your Parker account Today!

Create one account to manage everything you do with Parker, from your shopping preferences to your application access.

Register now

Parker's NTA compression style air brake fittings meet D.O.T. FMVSS 571.106 specifications and the functional requirements of SAE J246 and SAE J1131.

Share / Email

Technical Specifications

Connection 2 Style:	na
Shape:	Tube support
Style:	Tube
Connection 1 Tube O.D. (inch):	3/8
Connection 2 Thread Size (inch):	na

Connection 3 Style:	na
Connection 3 Thread Size (inch):	na
Connection 2 Tube O.D. (inch):	na
Connection 1 Style:	Insert
Minimum Operating Temperature:	-40 °F, -40 °C
Maximum Operating Temperature:	200 °F, 93 °C
Maximum Operating Pressure:	150 psi, 10 bar
Tube Material:	SAE J844 Type A & B Nylon Tubing, Stainless Steel
Application:	Air Brake, Accessories
Body Material:	Brass
Nut Material:	Brass
Sleeve Material:	Brass
Thread Sealant Material:	Vibra-Seal 516
Specifications Met:	DOT FMVSS 571.106, SAE J1131, SAE J246

 **WARNING:** This product can expose you to chemicals including **Nickel and Nickel Compounds** which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE. This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise. The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors. To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems..... [Click here to view all product safety information.](#)

Based on your experience finding this product today, how likely are you to recommend Parker Hannifin to a friend or colleague?

Not at all likely

Extremely likely

0

1

2

3

4

5

6

7

8

9

10

Item Information

Being the world's leader in leak free technologies Parker's NTA fittings utilize a ribbed sleeve for compression and positive grip. NTA fittings meet SAE J246, SAE J1131 and D.O.T. FMVSS571.106 specifications. NTA fittings have a pre-applied thread sealant on all male pipe threads. Electroless nickel plated bodies can be used with bio-diesel.

Use with the following Parker Parflex Division J844 tubing

- 1120 Nylon Air Brake Tubing
- 1320 Quantum Elastomeric Air Brake Tubing

... .